

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

## SPECIFICATIONS

EFFECTIVE WIDTH: 6"- 48"

BEGINNING ELEVATION: 7" - 120" LENGTH: 36" - 240"

**ENDING ELEVATION:** 7" - 120" **SPEED:** 15 - 110 FPM

ROLLER CENTERS: 3", 4", 6"

**DRIVE:** Standard drive is mounted near the center of the conveyor length on belt guard side. Up to 20 conveyor rollers can be driven from each side of the drive roller. Additional drives are required to extend the conveyor length.

**FRAME**: <u>Standard</u> frame includes 5" channel on chain box side and 3-1/2" channel on opposite side with roller set high in frame. <u>Optional</u> frame includes 5" channel on opposite side with roller set low in frame.

**MOTOR:** 1/2 HP through 2 HP, Energy efficient and inverter duty motors are also available along with Motorized Drive Rollers (MDR). voltages include 115/1/60, 208/3/60, 230/3/60, 460/3/60 and 575/3/60 along with DC voltages for MDR drives.

**ROLLERS:** Standard galvanized roller - 1.90" diameter, 16 ga wall tube with 7/16" hex cold rolled steel axles, spring retained. Standard bearings are ABEC precision, grease packed. Rollers include Poly-V sleeves for (4) rib belts.


**ROLLER COVERS:** Optional roller covers include polyurethane roller sleeves, Ultrex accumulation sleeves.


**SUPPORT CENTERS:** Standard supports are heavy duty floor supports on 10' centers. Optional 4" formed channel with jack bolt adjustment.

**FRAME FINISH:** <u>Standard</u> finish is OSHA safety blue powder. <u>Optional</u> colors include green, beige, gray, orange, black and yellow.

1







ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.