

# **Belt Conveyors**



# MDRB – Medium Duty Roller Bed with 1.90" Diameter Rollers

Model MDRB is a medium duty, roller bed belt conveyor designed for wide applications. These conveyors are capable of moving heavier loads with less power than typical slider bed belt conveyors.

# **Belt Width**

• 12", 18", 24", 30", 36", 42", 48"

#### Length

• 60" to 1,200"

#### Belt

- PVC120 EMB embossed cover with clipper lacing.
- Optional:
  - PVC120 smooth top
  - o PVC150 rough top
  - PVC120, Black, friction both sides
  - PVC Food grade, White
  - Thermoplastic polyurethane (TPU) Covered Belt
  - PVC longitudinal groove
  - o No Belt
- Troughed Belts design also available.

# **Drive Location**

- End Drive, Bottom Right
- Optional:
  - End Drive, Bottom, Left
  - End Drive, Side, Right or Left
  - Center Drive, Right or Left (standard for conveyors with reverse)

# Motor

- 1/2 HP to 2 HP
- Totally Enclosed Fan Cooled motor
- Optional:
  - $\circ$  Inverter Duty motor
  - Power Off Brake motor
- Voltage: 230/460/ 3Ph/ 60hz
- Optional:
  - o 115V/ 1Ph/ 60Hz
  - o 208V/1Ph/60Hz
  - 230V/ 1Ph/ 60Hz
  - 575V/ 3Ph/ 60Hz
  - 。 90V DC

# Speed

- 15 to 300 FPM (feet per minute)
- Reverse capability optional

# **Control Options**

- No controls (provided by others)
- Variable Speed Controller
- Combination motor starter with disconnect, fixed speed
- Combination motor starter with disconnect, variable speed
- PLC with HMI

# **Conveyor Color**

- Blue (RAL 5017)
- Guards are yellow (RAL 1023)
- Moving parts are bright red orange (RAL 2008).
- Optional:
  - o Light Gray (RAL 7035)
  - Repose Gray (not an RAL)
  - o Patina Green (RAL 6000)
  - Signal White (RAL 9003)
  - $\circ~$  Jet Black (RAL 9005)
  - Flat Black (not an RAL)
  - Custom colors available


# **Additional Options**


- Conveyor Supports with or without casters
- Guardrail
- Photo Eye Sensor(s)
- Custom sizes and features available. Please consult a LEWCO Applications Engineer for more information.


#### **Quality Assurance**

- Each unit comes complete with a (1) year warranty.
- Manufactured under ISO 9001 Quality Certified System.










SECTION C-C



- 19.5" -

OPTIONAL TROUGH CONSTRUCTION

