



**OPERATION:** Push hand valve for pressure (handle will stay in position). Push valve opposite way to exhaust pressure.

### SPECIFICATIONS

**VALVE:** Hand operated valve has 1/4" NPT ports, 2-position, 4-way, maintained/detended. Part # PCP5368. Optional spring-return handle (model VS1-SPRING) or solenoid actuated valve (model VS1-S).

**FILTER, REGULATOR, LUBRICATOR (FRL)** with 3/8" ports. Includes fittings. Part #: PCP4616

**TUBING:** Includes 20 Ft. of orange & 20 Ft. of blue 1/4" polyurethane tubing.

**AIR REQUIREMENTS:** 80 PSI minimum pressure to 115 PSI maximum pressure.

**MOUNTING:** Lags to floor with 3/8" anchors bolts (not included).

**NOTE:** System pressure loss can occur over extended periods with no use.

**MODEL:** VS1

**DESCRIPTION:** VALVE STAND, HAND VALVE

LEWCO, INC. IS COMMITTED TO CONTINUOUS IMPROVEMENT AND RESERVES THE RIGHT TO CHANGE DESIGNS AND SPECIFICATIONS WITHOUT NOTICE.

THIS DRAWING MUST NOT BE COPIED, REPRODUCED OR USED FOR ANY PURPOSE WITHOUT THE WRITTEN CONSENT OF LEWCO, INC. ALL RIGHTS RESERVED.

**LEWCO**

706 LANE ST. SANDUSKY, OH 44870, U.S.A.